

120-26








## PRODUCT FEATURES


- Style: Transitional
- Collection: Transition
- Temperature Controlled By Pressure Balance
- Cross Handles


# ■ TECHNICAL DETAILS


Access Hole Diameter: 5"
Handle Turn Angle: 115°
Spout Reach: 7 1/2"
Connection Type: Female 1/2" NPT Connection
Installation Type: Wall Mounted
Primary Material: Brass
Valve Material: Ceramic
Shower Flow Restriction: 1.8 gpm
Spout Flow Restriction: Full Flow
Water Pressure Maximum: 85 PSI
Water Pressure Minimum: 20 PSI
Water Pressure Recommended: 60 PSI


### PRODUCT DIMENSIONS















#### www. phylrich.com

1261 Logan Avenue, Costa Mesa, California 92626. Phone: 714.361.4800 Fax: 714.617.3120



ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC



120-27



### PRODUCT FEATURES


- Style: Transitional
- Collection: Transition
- Temperature Controlled By Pressure Balance
- Lever Handles


.


# ■ TECHNICAL DETAILS


Access Hole Diameter: 5"
Handle Turn Angle: 115°
Spout Reach: 7 1/2"
Connection Type: Female 1/2" NPT Connection Installation Type: Wall Mounted Primary Material: Brass
Valve Material: Ceramic
Shower Flow Restriction: 1.8 gpm
Spout Flow Restriction: Full Flow
Water Pressure Maximum: 85 PSI
Water Pressure Minimum: 20 PSI
Water Pressure Recommended: 60 PSI


















#### www. phylrich.com

1261 Logan Avenue, Costa Mesa, California 92626. Phone: 714.361.4800 Fax: 714.617.3120



ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC