

Outdoor Sconce 1Lt Fluorescent BK

10622BK (Black (Painted))

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	9.50"
Width	10.00"

Ordering Information

Product ID	10622BK
Finish	Black (Painted)
Available Finishes	BK, WH

Dimensions

Extension	5.00"
Height from center of Wall opening	4.50"
Base Backplate	9.00 DIA
Weight	4.00 LBS

Photometrics

Kelvin Temperature	2700K
--------------------	-------

Specifications

Material	Glass
Glass Description	Frosted Ribbed

Electrical

Voltage	120V
---------	------

Qualifications

Safety Rated	Wet
Title 24	Yes
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	Compact Fluorescent
Lamp Included	Included
Number of Lights/LEDs	1
Max or Nominal Watt	18W
Socket Wire	105
Socket Type	GU24
Lamp Type	GU24
Bulb Product ID	4044

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

Outdoor Sconce 1Lt Fluorescent WH

10622WH (White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	9.50"
Width	10.00"

Ordering Information

Product ID	10622WH
Finish	White
Available Finishes	BK, WH

Dimensions

Extension	5.00"
Height from center of Wall opening	4.50"
Base Backplate	9.00 DIA
Weight	4.00 LBS

Photometrics

Kelvin Temperature	2700K
--------------------	-------

Specifications

Material	Glass
Glass Description	Frosted Ribbed

Electrical

Voltage	120V
---------	------

Qualifications

Safety Rated	Wet
Title 24	Yes
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	Compact Fluorescent
Lamp Included	Included
Number of Lights/LEDs	1
Max or Nominal Watt	18W
Socket Wire	105
Socket Type	GU24
Lamp Type	GU24
Bulb Product ID	4044

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.