

Outdoor Wall 1Lt Fluorescent AZ

10640AZ (Architectural Bronze)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	10.25"
Width	9.25"

Ordering Information

Product ID	10640AZ
Finish	Architectural Bronze
Available Finishes	NI, AZ

Dimensions

Extension	3.75"
Height from center of Wall opening	5.50"
Base Backplate	4.25 X 7.75
Weight	2.15 LBS

Photometrics

Kelvin Temperature	2700K
--------------------	-------

Specifications

Material	Aluminum
Glass Description	White Pc Diffuser

Electrical

Voltage	120V
---------	------

Qualifications

Safety Rated	Wet
Title 24	Yes
ADA Compliant	Yes
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	Compact Fluorescent
Lamp Included	Included
Number of Lights/LEDs	1
Max or Nominal Watt	18W
Socket Wire	105
Socket Type	GU24
Lamp Type	GU24
Bulb Product ID	4044

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

Outdoor Wall 1Lt Fluorescent NI

10640NI (Brushed Nickel)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	10.25"
Width	9.25"

Ordering Information

Product ID	10640NI
Finish	Brushed Nickel
Available Finishes	AZ, NI

Dimensions

Extension	3.75"
Height from center of Wall opening	5.50"
Base Backplate	4.25 X 7.75
Weight	2.15 LBS

Photometrics

Kelvin Temperature	2700K
--------------------	-------

Specifications

Material	306 Stainless Steel
Glass Description	White Pc Diffuser

Electrical

Voltage	120V
---------	------

Qualifications

Safety Rated	Wet
Title 24	Yes
ADA Compliant	Yes
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	Compact Fluorescent
Lamp Included	Included
Number of Lights/LEDs	1
Max or Nominal Watt	18W
Socket Wire	105
Socket Type	GU24
Lamp Type	GU24
Bulb Product ID	4044

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.