

Commercial Flushometer Back Spud Wall-Hung Toilet – 1.0/1.28/1.6 GPF

FEATURES

- Wall-mounted
- Elongated front bowl
- Optional CeFiONtect™ glaze prevents debris from sticking to ceramic surfaces, making them easier to clean
- Clear glazed trapway coating

MODELS

- CT708UV
Commercial wall-mounted toilet with 1-1/2' back spud inlet, less seat
- CT708UVG
Commercial wall-mounted toilet with 1-1/2' back spud inlet, less seat with CeFiONtect ceramic glaze



ADDITIONAL ITEMS

- SC534 seat
- SC134 seat
- THU111 Retro-fit mounting bolt cap set (4 pcs)

ECOPOWER® FLUSH VALVES	
Concealed 14" x 12"	
TET2UA31#CP	1.0 GPF
TET2LA31#SS	1.28 GPF
TET2GA31#SS	1.6 GPF
Concealed 4" x 4"	
TET3UA31#SS	1.0 GPF
TET3LA31#SS	1.28 GPF
TET3GA31#SS	1.6 GPF

COLORS/FINISHES

- Standard
#01 Cotton

PRODUCT SPECIFICATION

The wall-mounted, low consumption siphon jet flushing toilet shall be 1.0, 1.28, or 1.6 GPF (3.8, 4.8, or 6.0 LPF) when paired with a flush valve of corresponding flush volume. Toilet shall have optional CeFiONtect ceramic glaze. Toilet can be mounted at ADA height. Toilet shall be TOTO Model CT708UV_____.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- ADA compliant



CT708UV(G)

Commercial Flushometer Back Spud Wall-Hung Toilet – 1.0/1.28/1.6 GPF

SPECIFICATIONS

Water Use	1.0/1.28/1.6 GPF (3.8/4.8/6.0 LPF)
Flush System	Siphon Jet Flushing Action
Water Surface	12" x 9-1/4"
Water Pressure	Min: 35 psi (Flowing) Max: 80 psi (Static)
Min. Flow Rate	24 GPM
Trap Diameter	2-1/8"
Trap Seal	2-5/8"
Material	Vitreous China
Warranty	One Year Limited Warranty
Shipping Weight	56 lbs
Shipping Dimensions	27-1/4" L x 15-5/8" W x 17-5/8" H

INSTALLATION NOTES

Spuds are unique for TOTO product. For replacement spuds, contact TOTO for part number THU073R

DIMENSIONS

