*** READ & SAVE THESE INSTRUCTIONS *** ACCESS LIGHTING MODEL 53340, 53341 INSTALLATION & OPERATION INSTRUCTIONS

(1) TOOLS AND MATERIALS REQUIRED

- ❖ BLADE SCREW DRIVER
- WIRE CUTTERS
- WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE
- ❖ 2 x 60W /E-26/medium base bulb/A-19 Bulb Attention: Before assembling your lighting fixture, please read the following instructions. If you feel you do not have sufficient electrical experience, refer to a do-it-yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

(2) GENERAL

- To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
- All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
- These fixtures are intended for mounting to a standard 4" x 2 ¼" deep metal octagon outlet box. The box must be directly supported by the building structure and U.L Recognized.
- Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

- Universal Crossbar
- Mounting Hardware and Universal Crossbar
- * Fixture Back Plate with socket
- 1 x Glass Diffuser
- 1 x Metal Diffuser

(4) PREPARE THE FIXTURE

Refer to attached illustration of fixture parts and assembly.

- If you are replacing an existing fixture disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
- Mount the Universal Crossbar to the Junction Box with the supplied Mounting Screws (1). Ensure that the two additional Screws are facing outward (away from the wall).
- Pull the Supply wires through the Center Hole in the Universal Crossbar.
- Connect the BLACK supply wire to the Black wire of the fixture with supplied Wire Nuts (2) ensuring a secure connection.
- 5. Connect the WHITE supply wire to the White wire from the fixture a secure with supplied Wire Nuts (2).
- Attach the ground (GREEN) wire from the fixture to the outlet box ground terminal (or to the box ground wire).
- 7. Secure all wire nuts connections with UL listed electrical tape. Tuck wires carefully into Junction box.
- 8. Secure the Fixture Back Plate to the junction box by placing the protruding screws from the Universal Crossbar through the designated holes in the Fixture Back Plate. Secure the Fixture Back Plate with the supplied Washers and Nuts (3).
- Insert 2 x E-26/Type A-19, medium base bulbs (4). DO NOT EXCEED WATTAGE SPECIFIED ON WARNING LABEL
- Position the Glass Diffuser (5) such that the Screws on the Metal Diffuser can be placed into the designated holes in the Glass Diffuser (5). Secure with the supplied plastic washers and nuts (6).
- 11. Fit the Diffuser Set (7)(Glass Diffuser and Metal Diffuser), up against the Fixture Back Plate. Insert the Screws on the Metal Diffuser into the tubes on the Fixture Back Plate. Use the supplied wrench to secure the diffuser set with the Allen Screws(8)
- 12. Fit the two flat glass(9) to both top and bottom of the fixture and secure with the screws(10).
- Restore electricity and check the operation of your new lighting fixture.

CAUTION:

- Ensure that the Fitting is Cool and Switched off, Before Changing the Bulb.
- Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label:



MODEL 53340, 53341



