

24 Pack Downlight LED 2700K WHT

43846WHLED27B (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 1.25" |
| Width | 7.50" |

Ordering Information

| | |
|--------------------|--------------------|
| Product ID | 43846WHLED27B |
| Finish | Textured White |
| Available Finishes | WHT, WHT, WHT, WHT |

Dimensions

| | |
|------------------------------------|----------|
| Height from center of Wall opening | 3.75" |
| Base Backplate | 7.50 DIA |
| Weight | 1.00 LBS |

Photometrics

| | |
|-----------------------|--------|
| Kelvin Temperature | 2700 K |
| Color Rendering Index | 90 |

Specifications

| | |
|----------------------|------------------------|
| Material | Steel |
| Diffuser Description | Polycarbonate Diffuser |

Electrical

| | |
|---------------|-------------|
| Dimmable | Yes |
| Voltage | 120 V |
| Input Voltage | Single(120) |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| ADA Compliant | Yes |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|------------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| # of Bulbs/LED Modules | 1 |
| Delivered Lumens | 850 |
| Dimming | Yes |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

24 Pack Downlight LED 3000K WHT

43846WHLED30B (Textured White)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 1.25" |
| Width | 7.50" |

Ordering Information

| | |
|--------------------|--------------------|
| Product ID | 43846WHLED30B |
| Finish | Textured White |
| Available Finishes | WHT, WHT, WHT, WHT |

Dimensions

| | |
|------------------------------------|----------|
| Height from center of Wall opening | 3.75" |
| Base Backplate | 7.50 DIA |
| Weight | 1.00 LBS |

Photometrics

| | |
|-----------------------|--------|
| Kelvin Temperature | 3000 K |
| Color Rendering Index | 90 |

Specifications

| | |
|----------------------|------------------------|
| Material | Steel |
| Diffuser Description | Polycarbonate Diffuser |

Electrical

| | |
|---------------|-------------|
| Dimmable | Yes |
| Voltage | 120 V |
| Input Voltage | Single(120) |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| ADA Compliant | Yes |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|------------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| # of Bulbs/LED Modules | 1 |
| Delivered Lumens | 850 |
| Dimming | Yes |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.