



INSTALLATION INSTRUCTIONS





1. Assemble seals (3) into the underbody (4)




- 3. Locate the underbody (4) and seals (3) central to the underside of the vessel sink hole
- 4. Locate the waste (2) central to the top side of the vessel sink hole
- 5. Assemble decorative cover (1) as per diagram, hand tighten + 1/4 turn.
- Note: Rubber washer is only used for glass sinks.




INSTALLATION INSTRUCTIONS 1.5" Dome Drain, DR120






1. Assemble seals (3) into



underside of the waste (2) 3. Locate the underbody (4) and seals (3) central to the underside of the vessel

100% Silicone (non-waterbased) to the



4. Locate the waste (2) central to the top side of the vessel sink hole

sink hole

- 5. Assemble decorative cover (1) as per diagram, hand tighten + 1/4 turn.
- Note: Rubber washer is only used for glass sinks.

Remove all excess silicone around the drain after the drain has been installed

W W W . N A T I V E T R A I L S . N E T

Remove all excess silicone around the drain after the drain has been installed

W W W . N A T I V E T R A I L S . N E T




INSTALLATION INSTRUCTIONS 1.5" Dome Drain, DR120




1. Assemble seals (3) into the underbody (4)



2. Apply a small bead of 100% Silicone (non-waterbased) to the underside of the waste (2)




3. Locate the underbody (4) and seals (3) central to the underside of the vessel sink hole




- 4. Locate the waste (2) central to the top side of the vessel sink hole
- 5. Assemble decorative cover (1) as per diagram, hand tighten + 1/4 turn.
- Note: Rubber washer is only used for glass sinks.




INSTALLATION INSTRUCTIONS 1.5" Dome Drain, DR120






2. Apply a small bead of 100% Silicone (non-waterbased) to the underside of the waste (2)



- 3. Locate the underbody (4) and seals (3) central to the underside of the vessel sink hole
- 4. Locate the waste (2) central to the top side of the vessel sink hole
- 5. Assemble decorative cover (1) as per diagram, hand tighten + 1/4 turn.
- Note: Rubber washer is only used for glass sinks.



Remove all excess silicone around the drain after the drain has been installed

W W W. N A T I V E T R A I L S . N E T

Remove all excess silicone around the drain after the drain has been installed W W W . N A T I V E T R A I L S . N E T