66" LUCINDA ACRYLIC SLIPPER TUB

Cat. No.

Features:

ATSN66F

No faucet holes
 No overflow
 IAPMO certified

available





L:	65-1⁄2"
W:	28-¾"
H:	23" - 28-3/4" (from floor to top
	of tub)

Water depth: 17-¹/₂" to top of tub Water depth: 13" to overflow

> The following is recommended for ATSN68f tubs: •Faucets: part #4602, #4604 or 7082

•Rigid, freestanding supplies: part #4502
•Leg tub drain: part #5599LT or 5599TS



Overflow can be drilled. With overflow drilled this tub requires drain 5599PD. **Tubs that have been drilled with overflow are "special order" and are not returnable.**

Gallon Capacity without OF:	50
Shipping Weight:	195 lbs.
Empty Weight:	105 lbs.
Filled Weight without OF:	568 lbs.



	● Ø 2-1/4 [°]
: 50 195 lbs. 105 lbs. 568 lbs	43-1/2"

COOPI Descri

Option to add foam insulation between tub walls


Tub is thoroughly inspected before shipment


Interior and exterior walls acrylic sheets

► Sleek contemporary design

► Air between sheets provides insulation to retain warmth

Custom Colors Available (inside of tub is always white enamel): Painted bathtubs are considered "special order" and are not returnable \$160 Bisque or Black \$250 Designer Color





Dimensions of fixture are nominal and specifications subject to change without notice.