COMPACT 545 PEDESTAL LAVATORY

CAT. NO

3-55X



	 Features: Made of Vitreous China Pre-drilled overflow Available for single hole (3-551), 4"centerset (3-554), 6" mini spread (3-556), or 8" widespread (3-558) Mounting Hardware Included For ease installation order Hangers (pair) or Bracket (one)
W: 21-1/2"	Colors: WH WhiteCompliance Certification Meets or exceeds the following specifications: ASME A112.19.2 2013 and CSA B45.1-13 for ceramic plumbing fixtures.
D: 16-1/8" H: 32-3/8"	21-1/2"
Column: 26-1/4"L x 6"W x 5-7/8"D	$16-1/8" \left(\begin{array}{c} \oplus \oplus \oplus \oplus \oplus \\ \oplus \\ \oplus \\ \end{array} \right) \left(\begin{array}{c} \oplus \\ \oplus \\ \oplus \\ \oplus \\ \end{array} \right) \left(\begin{array}{c} \oplus \\ \oplus \\ \oplus \\ \oplus \\ \oplus \\ \end{array} \right) \left(\begin{array}{c} \oplus \\ \oplus \\ \oplus \\ \oplus \\ \oplus \\ \oplus \\ \end{array} \right) \left(\begin{array}{c} \oplus \\ \end{array} \right) \left(\begin{array}{c} \oplus \\ \oplus $
Back of basin to center of faucet:2-1/2"Back of basin to center of drain:7-1/2"Mount bolts height:30-1/2"Mount holes cc:11"	
Interior Dimensions:	32-3/8"
Basin Interior:19-1/4" x 10-1/2"Basin Depth:6"Faucet and spout holes:1-3/8"	

Dimensions of fixture are nominal and may vary within the range of tolerances established by ASME Standard A112.19.2-2013. Dimensions and specifications subject to change without notice.