

GEBERIT SIGMA60 ACTUATORS

For Sigma Concealed Tanks, 2x6 and 2x4 Installations

SPECIFICATIONS

Actuators for concealed tank and carrier system. Actuator flush plates and push buttons shall be glass, zinc die-cast, and plated to guard against scratches. For tile, stone or other hard surfaced walls only. All components shall be compliant with applicable codes and product standards.

FEATURES

- Designed to maintain appearance push after push
- Moving parts are accessible behind actuator flush plate
- · Made of glass, zinc die cast and plated
- Available in a variety of unique combinations of finish/color
- Incorporates water saving possibilities when used with Geberit dual-flush tanks
 1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or
 1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Includes mounting frame and hardware

WARRANTY

One-year limited warranty.

ક Dual-Flush Actuators, Sigma 2x6 and 2x4 Installation Style Material Finish Model No. 115.640.GH.1 Sigma60 Die Cast Brushed chrome White Glass 115.640.SI.1 Black Glass 115.640.SJ.1 115.640.SQ.1 Umber Glass Rough-in set (REQUIRED accessory 243.168.00.1 for Sigma 2x6 concealed tanks) Cover frame (optional accessory) 115.641.21.1 Polished Chrome Cover frame (optional accessory) 115.641.GH.1

DIMENSIONS

Products marked with comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



Date:	Quantity:
Model Specific	ed:
Variations Spe	ecified:
Customer/Wh	olesaler:
Contractor:	
Architect:	



Geberit 2100 S. Clearwater Drive Des Plaines, IL 60018 USA

P 847-803-7777 F 847-803-5454

www.geberit.us