

# Ambiance™ Mirrored Cabinet

Product Specifications: Residential

**ELECTRIC MIRROR®**



## PRODUCT DESCRIPTION

Add Ambiance™ to your bathroom space and create a uniquely modern look with real-world functionality. It features a frame of lustrous light and a precision polished edge — an ideal match for your contemporary décor.

## SPECIFICATION STATEMENT

Solution shall consist of a lighted mirrored cabinet with forward-facing task lighting and corrosion-resistant glass. Mirror shall have built-in defogger for fog-free operation. Mirror will have LEDs with greater than or equal to 90 CRI (color rendering index), and a 3-year limited warranty.

## THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

## FEATURES AND BENEFITS

- Copper-free, corrosion-resistant glass
- Forward-facing task lighting in the mirror door
- Integrated defogger<sup>1</sup>
- Mirrored interior with top light
- Adjustable glass shelves
- Matte silver aluminum cabinet body
- Interior 20 Amp, 120VAC GFCI receptacle
- Two electrical outlets and four USB Ports
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- Surface mounting kit included
- Title 24 compliance available
- 3-year limited warranty
- Covered by one or more patents

## AVAILABLE OPTIONS

- Ganging Kit for installation of side-by-side cabinets
- Left- or right-hand door

## LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- 0-10V dimmable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 492 lumens per foot
- Calculated L<sub>70</sub> 52,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

## SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards

<sup>1</sup> See technology specification sheets for more information.

## INSTALLATION SPECIFICATIONS

- 120V hardwire electrical connection; provide 12" whip; junction box not required; interior 20 Amp, GFCI outlet should be on a 120V, 20 Amp unswitched circuit; refer to installation instructions for further details and options
- Cabinet can be recess-mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch or with a forward-phase dimming switch
- Mirror can only be hung in the WxH orientation as show and is not field interchangeable

## MODELS

Base Model with Left Hinge*	Base Model with Right Hinge*	Dimensions	Rough-in Dimensions	Power Requirements**
AMB-2330-LT	AMB-2330-RT	23.25"W x 30.00"H x 4.77"D (590mm x 762mm x 122mm)	22.38"W x 28.63"H (568mm x 727mm)	120/240 VAC, 78W
AMB-2340-LT	AMB-2330-RT	23.25"W x 40.00"H x 4.77"D (590mm x 1016mm x 122mm)	22.38"W x 38.63"H (568mm x 981mm)	120/240 VAC, 89W

\*Base, recess-mounted model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

\*\* Power requirements include defogger power.

## DIMENSIONAL DRAWING (Not to scale)

Total cabinet depth is 4.77" (119mm). The recessed depth is 3.73" (95 mm).  
 Recommend minimum 4" wall depth space.  
 Depth after recessed installation is 0.97" (25 mm).

