



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Forward-phase dimming technology
- Enclosed chassis
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Ava™ Technology 1
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- CCT: 2,700K, 4,600K, 6,500K color rotation (with Ava)
- Replaceable LEDs
- 604 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ See technology specification sheets for more details

PRODUCT DESCRIPTION

By uniting a romantic shape with a stunning circle of brilliant light, we created an Eternity™ that encapsulates a clear vision of renewal and balance, boldly illuminating your space with timeless elegance.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using dimmable, replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S and global components and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 20 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S. based customer service support
- ✓ 125,000 square foot American manufacturing facility

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Ava model controlled by capacitive touch button on fixture or non-dimming on/off wall switch
- Non-Ava model controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model	Base Model with Ava	Dimensions	Power Requirements
ETE-2130	ETE-2130-AE	21"W x 30"H x 1.75"D (533mm x 762mm x 44mm)	120/240 VAC, 58W
ETE-30	ETE-30-AE	30" diameter x 1.75"D (762mm x 44mm)	120/240 VAC, 75W
ETE-36	ETE-36-AE	36" diameter x 1.75"D (914mm x 44mm)	120/240 VAC, 94W

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

