

# Pax<sup>™</sup> Series Zero-Radius Stainless Steel Topmount Kitchen Sinks

KP1TS25S-1

KP1TS33S-2

KP1TS33S-4

# Thank you for your purchase

We would like to take this opportunity to thank you for choosing Kraus. We hope that you are completely satisfied with your purchase, and enjoy it for years to come. If you have any questions, or require technical assistance, please contact us at 800.775.0703 and one of our representatives will be happy to help.

For more information about Kraus products, please visit:

#### www.kraususa.com

In order to activate your warranty and get faster access to customer support, please register your new Kraus product at:

www.kraususa.com/registration

Sincerely,

Kraus USA Customer Service

#### **Prior to Installation:**

- Make sure that you have all necessary parts by checking the parts list. If any part is missing or damaged, please contact Kraus Customer Service at 800-775-0703 for a replacement
- Inspect the sink prior to installation to make sure that it has not been damaged or during shipping
- Use the cut-out template provided by Kraus
- Observe all plumbing and building codes according to your state requirements


For technical assistance or replacement parts, please contact Kraus

Customer Service and one of our representatives will be happy to help:

Toll-Free: 800-775-0703 or customerservice@kraususa.com

The step-by-step guidelines in the installation instructions are a general reference for installing a Kraus sink. Should there be any discrepancies, Kraus cannot be held liable. It is recommended to install all Kraus products by hiring a licensed professional.

# Tools you will need:





**NOTE:** Specialized tools may be necessary to install Kraus stainless steel topmount sinks with countertop materials other than wood, marble, or granite

#### **Parts List**

- Cut-Out Template
- Mounting Hardware
- Bottom Grid
- Drain


## **Dimensions**





KP1TS25S-1 25" x 22" x 9"

Min Cabinet Size: 27" Drain Model #: ST-1 KP1TS33S-2 33" x 22" x 9" Min Cabinet Size: 36" Drain Model #: ST-1




KP1TS33S-4 33" x 22" x 9"

Min Cabinet Size: 36" Drain Model #: ST-1

# 1. Position Template


- Check the cut-out template against the actual sink to ensure a proper sized cut-out
- Place the cut-out template in the desired location on the countertop

**NOTE:** Make sure clearance is suitable for backsplash, faucet, and plumbing for the sink



# 2. Trace Template

• Trace template on countertop with a pencil




# 3. Cut Countertop

• Cut the opening in the countertop by carefully following the traced line


**NOTE:** Please use the appropriate saw that best fits your countertop material






# 4. Attach Mounting Hardware

- Attach mounting hardware to the prongs protruding from the underside of the sink rim
- Make sure the hooked side of the mounting clip is facing away from the sink




# 5. Apply Silicone or Plumber's Putty

- Clean and dry the surface around the opening of the sink
- Turn the unit upside down to apply sealant. Apply silicone-based sealant (not included) underneath the edge of the sink




## 6. Secure Sink to Countertop

- Insert the sink into the opening, check the alignment of the sink to the cutout in the countertop, and press firmly
- Tighten the screws in the front of the sink, followed by the ones in the back and on the sides of the sink
- Remove excess silicone-based sealant
- Allow sealant to set for 30-60 minutes



# 7. Install Plumbing Fixtures

- Connect drain to sink. Connect trap to drain. Connect water supply connections to faucet according to manufacturer's instructions
- Run water into sink and check for leaks



#### Maintenance

Clean your sink on a regular basis with warm soapy water. Rinse the sink after using cleaning products. Wipe the sink surface with a soft cloth to remove any liquid residue. Do not cut food directly on the surface of the sink. Do not leave sharp objects on the surface of the sink for an extended period of time. Do not use abrasive cleaning products, sanding tools, steel wool, or bleaching products

### **Codes/Standards Applicable:**



#### **Kitchen Sink Warranty**

Kraus products are manufactured and tested to the highest quality standards by Kraus USA Inc. ("Kraus"). Kraus extends this warranty to the original purchaser for personal household use of the "Kitchen Sink" in its original location. The warranty is non-transferable.

Kraus warrants the structure and finish of the product to be free from defects in material and workmanship under normal usage for the lifetime of the product. The warranty commences from the initial date of purchase by the owner or trade professional, from an authorized Kraus dealer, through the lifetime of the original owner or end-user.

Any product reported to the authorized dealer or to Kraus as being defective within the warranty period will be repaired or replaced with a product of equal value at the option of Kraus. This warranty extends to the original owner or end-user, and is not transferable to a subsequent owner.

#### Restrictions

This warranty does not cover antediluvian, discontinued, or display products, whether such items are purchased at discount outlets, unauthorized dealers, and/or sold on clearance.

This warranty does not cover instances of negligence, misuse, abuse, improper installation, carelessness, accident, hard water or mineral deposits, exposure to corrosive materials, misapplication, damages caused by improper maintenance, alteration of the product, or failure to follow care or installation instructions enclosed with your product. Avoid using abrasive cleaners such as powders, bleach, ammonia, alcohol, or chlorine. Avoid using abrasive pads, steel wool, or wire brushes, as these will damage and wear down the finish.

This warranty does not apply to Products that have not been installed or operated in accordance with instructions supplied by Kraus and all applicable rules, regulations, and legislation pertaining to such installations.

This warranty does not apply unless the Kraus product is installed by a fully insured and licensed trade professional. Kraus insists that such professionals have experience in the installation of bathroom and kitchen manufactured goods.

This warranty does not cover labor charges or costs of removal and reinstallation of said product. This warranty does not allow recovery of incidental or consequential damages, such as loss of use, delay, property damage, or other consequential damages, and Kraus accepts no liability for such damages.

# Due to the nature of drain usage, there is no finish warranty on any drain product (including pop-up drains, lavatory drains, and kitchen drains)

This warranty does not cover Marine or Outdoor Installation.

Except as otherwise provided above, Kraus makes no warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose, or compliance with any code.

Shipping charges will be covered for the first (1) year of the warranted replacement part or product (HI, AK, and Puerto Rico shipping charges may apply). International shipping fees are not included.

#### **Commercial Warranty**

Kraus extends the above warranty for a period of one (1) year to purchasers of products for industrial, commercial, and business use.

All incidental or consequential damages are specifically excluded. No additional warranties, express or implied are given, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose.

Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

#### If you are a homeowner please contact a Kraus Customer Service Representative at:

Kraus USA, Inc. 12 Harbor Park Drive Port Washington, NY 11050 Toll-free 800-775-0703 Customerservice@kraususa.com

# If you are a plumbing contractor or trade professional please contact a Kraus Pro Representative at:

Kraus USA, Inc. 12 Harbor Park Drive Port Washington, NY 11050 516-801-8955 Proservice@kraususa.com

#### If you are an Authorized Partner please contact a Partner Support Representative at:

Kraus USA, Inc. 12 Harbor Park Drive Port Washington, NY 11050 516-801-8954 Partnersupport@kraususa.com

#### In requesting warranty service, please be ready to provide:

- 1. Proof of purchase.
- 2. A description of the problem.

#### **REGISTER YOUR PRODUCT TODAY**

# **Receive** Proof of Ownership **Access** Customer Care & Installation Help **Get** Exclusive Kraus Offers & Promotions



Scan to Register Online or visit http://www.kraususa.com/registration

# We're always looking for ways to improve.

Please take a moment to share your experience. Visit http://www.kraususa.com/review to let us know what you think about your new Kraus product.

Contact Us to Learn More 1.800.775.0703 / www.kraususa.com / customerservice@kraususa.com Like & Follow KrausUSA

> Download the Kraus Care & Maintenance Guide at: http://www.kraususa.com/maintenance















# Single Lever Pull-Down Kitchen Faucet

**KPF-1630** 

# Thank you for your purchase

We would like to take this opportunity to thank you for choosing Kraus. We hope that you are completely satisfied with your purchase, and enjoy it for years to come. If you have any questions, or require technical assistance, please contact us at 800.775.0703 and one of our representatives will be happy to help.

For more information about Kraus products, please visit:

#### www.kraususa.com

In order to activate your warranty and get faster access to customer support, please register your new Kraus product at:

www.kraususa.com/registration

Sincerely,

Kraus USA Customer Service


#### **Prior to Installation:**

- Make sure you have all necessary parts by checking the diagram and parts list. If any part is missing or damaged, please contact Kraus Customer Service at 800-775-0703 for a replacement
- Turn off the cold and hot water at the angle stops and turn on the old faucet to release any built up pressure
- Flush angle stops to release any debris prior to installation
- Pre-drilled hole size requirement: 1-3/8" (min) 1-1/2" (max)
- Max countertop thickness: 1-3/8
- 1, 2, or 3 hole installation

For technical assistance or replacement parts, please contact Kraus Customer Service and one of our representatives will be happy to help:

Toll-Free: 800-775-0703 or Customerservice@kraususa.com

# **Diagram and Parts List**



## **Diagram and Parts List**

- 1. Spray Head
- 2. Faucet Body
- 3. Deck Plate Assembly
  - A. Deck Plate
  - B. Base Plate
- 4. Mounting Hardware
  - A. Rubber & Metal Washer
  - **B.** Mounting Nut
  - C. Mounting Screws
- 5. Spray Hose
- 6. Weight
- 7. Check Valve
- 8. Hot and Cold Copper Lines
  - A. Cold
  - B. Hot
- 9. Aerator Key
- 10. Hex Wrench
- 11. Faucet Extender
- 12. Washer

# Tools you will need



Adjustable Wrench






**Phillips Screwdriver** 



**Safety Goggles** 


# **Faucet Installation Procedure**



# **Installer Tip:**


Shut off main water supply before installing new faucet

# **Step 1: Remove mounting hardware**




Remove the mounting screws (4C), mounting nut (4B), and rubber & metal washer (4A) from the mounting pipe

Step 2A: Faucet installation - with deck plate




For three-hole installation: Deck plate (3A), base plate (3B), and silicone sealant (optional) are required

# Step 2B: Faucet installation - without deck plate




For single-hole installation: Deck plate (3A), base plate (3B), and silicone sealant are **NOT** required

Step 3: Install faucet and mounting hardware




Insert faucet body (2) into hole in countertop or deck plate assembly (3). Install mounting hardware (4A, B &C) from underneath the countertop

# **Step 4: Secure mounting hardware**




Adjust direction of faucet body (2) so that handle is on right side of faucet. Tighten mounting nut (4B) until snug. Tighten mounting screws (4C) to nut with a Phillips screwdriver until snug

Step 5: Attach spray hose and counterweight




Connect spray hose (5) to check valve (7) attached to supply line. Install weight (6) on lowest vertical point on spray hose (5)

# **Step 6: Connect waterlines**



Step 7: Flush spray hose

Connect waterlines (not included) to hot and cold copper lines (8). Connect waterlines (not included) to angle stops. Tighten both ends of waterlines with a wrench until snug. Turn on hot and cold angle stops and check for leaks



**Step 8 Check for leaks** 


Remove spray head (1) from spray hose (5). Hold tip of spray hose (5). Turn faucet on and let the water run for 60 seconds to flush any debris

NOTE: Please make sure washer (12) is installed attaching spray head to hose



Check for leaks at the connections. Retighten if necessary

## **Replacement Parts**



- 1. a. Aerator
  - b. Spray Head
- 2. Check Valve
- 3. Spray Hose
- 4. Hose Guide
- 5. Handle Button
- 6. Set Screw
- 7. Metal Handle
- 8. Cartridge Cover
- 9. Locking Nut
- 10. Cartridge
- 11. Cartridge Housing
- 12. Deck Plate
- 13. Base Plate
- 14. Rubber & Metal Washer
- 15. Mounting Nut
- 16. Mounting Screws
- 17. Protective Sleeve
- 18. Weight
- 19. Aerator Key
- 20. Faucet Extender
- 21. Hex Wrench
- 22. Check Valve
- 23. Connector
- 24. Washer

# **Care & Maintenance**

\*To keep the product clean & shining, follow the steps below:

- 1. Rinse with clean water & dry with a soft cloth
- 2. Do not clean with soaps, acid, polish, abrasives, or harsh cleaners
- 3. Do not use cloth with a coarse surface
- 4. Unscrew the aerator and clean when necessary


<sup>\*</sup>This installation manual is subject to change without further notice.

# **Trouble - Shooting**

If you have followed the instructions carefully and your faucet still does not work properly, take the following corrective steps:

| PROBLEM                                    | CAUSE  | ACTION   |
|--|--|--|
| Leakage under faucet<br>handle             | Locking nut has come<br>loose or cartridge<br>needs to be reseated               | Remove button located at top of handle. Loosen set screw with hex wrench. Remove handle and unscrew cartridge cover by hand. Tighten locking nut with an adjustable wrench   |
| Water does not shut off completely         | Cartridge may need to<br>be adjusted or replaced                                 | Remove button located at top of handle. Loosen set screw with hex wrench. Remove handle and unscrew cartridge cover by hand. Unscrew locking nut with an adjustable wrench. Remove ceramic disc cartridge. Check for cracks, and if O-ring is seated correctly. Reseat cartridge |
| Leaking between spray<br>head and the hose | Spray head may be loose or washer is not seated correctly in the hose connection | Tighten spray head by<br>hand until snug. Make<br>sure washer is seated<br>correctly   |
| Hose does not retract                      | Weight may be installed incorrectly  | Readjust weight on hose  |
| Low flow                                   | Aerator may be clogged   | Unscrew aerator with<br>aerator key. Hold tip of<br>spray head and turn on<br>water to flush debris  |


# **Maintenance - Cartridge Replacement**



Step 1: Remove button located at the top of the handle. Loosen the set screw with a hex wrench. Remove the handle and unscrew cartridge cover by hand



**Step 2:** Unscrew the locking nut with an adjustable wrench. Remove ceramic disc cartridge



**Step 3:** Place the new cartridge in the handle seat. Secure the cartridge with the locking nut and assemble the handle

## **Codes/Standards Applicable:**



NSF/ANSI Standard 61 certified by IAPMO NSF/ANSI Standard 372 certified by IAPMO







Meets ASME A112.18.1M/A112.18.1 1.75GPM 6.6L/min maximum

#### **HELP LINE**

Our customer service hours are Monday – Friday, 9am – 8pm EST. Be sure to visit our website at www.kraususa.com

#### If you are a homeowner please contact a Kraus Customer Service Representative at:

Kraus USA, Inc.
12 Harbor Park Drive
Port Washington, NY 11050
Toll-free 800-775-0703
Customerservice@kraususa.com

#### If you are a plumbing contractor or trade professional please contact a Kraus Pro Representative at:

Kraus USA, Inc. 12 Harbor Park Drive Port Washington, NY 11050 516-801-8955 Proservice@kraususa.com

#### If you are an Authorized Partner please contact a Partner Support Representative at:

Kraus USA, Inc.
12 Harbor Park Drive
Port Washington, NY 11050
516-801-8954
Partnersupport@kraususa.com

#### In requesting warranty service, please be ready to provide:

- 1. Proof of purchase.
- 2. A description of the problem.

# Download the Kraus Care & Maintenance Guide at:

http://www.kraususa.com/maintenance



#### **REGISTER YOUR PRODUCT TODAY**

# **Receive** Proof of Ownership **Access** Customer Care & Installation Help

**Get** Exclusive Kraus Offers & Promotions



Scan to Register Online or visit http://www.kraususa.com/registration

# We're always looking for ways to improve.

Please take a moment to share your experience.

Visit http://www.kraususa.com/review to let us know what you think
about your new Kraus product.

Contact Us to Learn More

1.800.775.0703 / www.kraususa.com / customerservice@kraususa.com

Like & Follow KrausUSA

Download the Kraus Care & Maintenance Guide at: http://www.kraususa.com/maintenance



