



L: 55-½" W: 29" H: 22"

Water Depth: 16-5/8" to top of tub Water Depth: 13-1/4" to overflow


Overflow slot: 3" under tub rim

The following is recommended for ATOV7H56B tubs:

Faucet:part #4061, 4603, 4062 or 4064

•Requires flexible Supplies

Gallon Capacity with OF: 45
Shipping Weight: 124 lbs.
Empty Weight: 75 lbs.
Filled Weight with OF: 449 lbs.



(Air jet configuration if system is added, more info on page 2.)

Features:

- ► Acrylic construction for lighter weight
- ► Air between sheet provides insulation to help retain warmth
- ► Overflow slot with integrated drain
- ▶ Drain and overflow covers included (available in 7 finishes)
- ▶7" centers on rim
- ►Tap Deck
- ▶ Option to add foam insulation between tub walls available
- ► New: Air jet system now available, more info on page 2


Finishes:

CP Polished ChromeBN Brushed NickelORB Oil Rubbed Bronze

WT White

PB Polished Brass PN Polished Nickel MB Matte Black

Custom Colors Available (inside of tub is always white enamel): Painted bathtubs are considered "special order" and are not returnable



Cat. No. AIR KIT 1, AIR KIT 2





- A AIR JET Bottom air jets for maximum bubble action.
- B BLOWER The heart of the massage system.
- MANIFOLD Double back flow security prevention device.
- D FLEXIBLE PVC HOSING IAPMO certified.
- E MAIN AIR INTAKE HOSE High temperature and pressure resistant.

Air Kit is installed in tub before shipment

Features:

- ▶ 750 Watt blower motor operates system
- ▶300 Watt air heater warms air
- ► System powered by 120V
- ▶ 16 brass air jets placed in bottom of tub
- ► Each air jet has 24 holes
- ► Air jet caps available in white (AIR KIT 1) or black (AIR KIT 2)
- ► Includes 1¼" x 3' main air hose plus 11/4" x 9' extension hose
- ► Automatic system purge after each use
- ► Automatic safety timer turns off system after 20 minutes
- ► Includes water tight remote control
- ► Compatible with most acrylic, copper and resin tubs with no feet
- ▶ Not available with cast iron tubs or tubs with feet





Remote

