



S29799

60W/LED/HID/MB/2700K/100-277V/EX39
 60 watt - LED HID Replacement; 2700K; Mogul extended base;
 Adjustable beam angle; 100-277 volts

Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- Built-in surge protection - 1KV
- 5 year limited warranty



S29799

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector [80-929](#)

Width (360°)	Width (270°)	Width (180°)
3.8"	8.2"	9.3"

Minimum Compartment Size		
Length	Width	Depth
8.27 inch	9.25 inch	9.25 inch

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent
S29799	Hi-Pro	045923297991	100 - 277	60	50/60Hz	500W	85W

HID Equivalent	Power Factor	Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches
250W	0.90	Mogul Extended	EX39	60W/LED/HID/MB/2700K/100-277V/EX39	Non-Dimmable	White	8-9/16"

MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Burning Position
---------------	----------------	---------------------	-------------	-------	-----	-----------------	------------------

3-13/16" (Open 9-5/16")	7320	50000	2700	Warm White	80+	Adjustable: 360; 270; 180	Up or Down Operation Only	
Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant	Fixture Type	UL Classification	Warranty
-20C (-4F) to a maximum of +65C (+149F)	12/6	Box	Lawful for sale in California	LM8IUGEJOHR DLC Search	Yes	Enclosed Rated	cULus - Wet Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

