

S29851

9WPLH/LED/835/DR/4P 9W LED PL 4-Pin; 3500K; 950 Lumens; G24q base; 50000 Average rated hours; 120 Deg. beam spread; Type A; Ballast dependent



Features

- Replaces 26, 32, and 42 watt CFLs
- Direct Replacement for use with Electronic, Instant Start, Rapid Start, and Programmed Start ballasts with no rewiring required. Ballast required.
- Instant on to full brightness / no flickering
- Horizontal operation
- Up to 70% energy saving
- Long life 50,000 hours
- 5 year warranty

*Ballast required (See Ballast Compatibility Chart)

View:

Ballast Compatibility Chart

Emergency Ballast Compatibility Chart

| 920 | Q 5 1 |
|-----|-------|
| 023 | noo i |

| Item Number | UPC | Watts | Fluorescent Equivalent | Lamp Shape | Base | Lamp Code | Dimmable/Non- Dimmable |
|----------------|--------------|-------|----------------------------|---------------|------|---------------------|---------------------------|
| S29851 | 045923298516 | 9 | 26, 32, and 42 watt CFL | PL | G24q | 9WPLH/LED/835/DR/4P | Non-Dimmable |

| Finish | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours | Kelvin Temp | Color | CRI |
|--------|---------------|---------------|----------------|---------------------|-------------|---------------|-----|
| Frost | 6-5/8'' | 1-3/32" | 950 | 50000 | 3500 | Neutral White | 82 |

| Beam Spread Deg | Operating Temperature | Package Type | CEC Status | DLC ID: | RoHS Compliant | UL or ETL Listed | UL Classification |
|-----------------------|---|-----------------|-------------------------------|----------------------------|-------------------|------------------------|--|
| 120 | -20C (-4F) to a maximum of +45C (+113F) | Box | Lawful for sale in California | PL8YPZRKJRQ3 DLC Search | Yes | Yes | cULus Classified - Damp Location Rated |

Warranty





National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051