
Ultra-slim LED Strip

Our ultra-slim linear can be seamlessly connected together creating a long, break-free light emission.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
LINU12	12"	4.3 W	400 lm	500 lm	90	3000 K	12 V

Specifications

- 12V DC LED driver required
- Dimmable with most low-voltage electronic dimmers
- 24" (60 cm) extension cord included
- Smooth linear wide spread
- Minimal heat emission
- No UV light emission
- Seamlessly interconnectable (No light breaks)
- Over 50,000 hours of service life

Finish

SBA Sandblasted aluminum

*Note:

Plug-in or hard-wired power supply required for installation. Sold separately.

Power supplies: plug-in

- ETR-LED10WPI**
12VDC/10W class 2 LED driver
- ETR-LED24WPI**
12VDC/24W class 2 LED driver

Power supplies: hard-wired

- BT06DIMLED-IC**
6W dimmable LED hardwire driver
- BT12DIMLED-IC**
12W dimmable LED hardwire driver
- BT24DIMLED-IC**
24W dimmable LED hardwire driver
- BT36DIMLED**
36W dimmable LED hardwire driver
- BT48DIMLED**
48W dimmable LED hardwire driver

Accessories

- LINU12-ACC-CROSS**
Illuminated cross-shaped connector
- LINU12-ACC-L-LEFT**
Illuminated L-shaped connector
- LINU12-ACC-L-RIGHT**
Illuminated L-shaped connector
- LINU12-ACC-T-LEFT**
Illuminated T-shaped connector
- LINU12-ACC-T-MIDDLE**
Illuminated T-shaped connector
- LINU12-ACC-T-RIGHT**
Illuminated T-shaped connector
- LINU12-EXT24**
24" extension cord
- LINU12-EXT108**
108" extension cord

Order example

LINU12
12" undercabinet linear with 400 lumens at 3000K in a sandblasted aluminum finish

LINU12

