24 110

GROHTHERM®

SINGLE FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM WITH CONTROL MODULE



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE TurboStat® compact cartridge with wax thermoelement
- Thermostatic temperature control with GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Volume control with ceramic disc stop valve, 120°
- 6 1/4" Metal wall trim plate with GROHE QuickFix® (concealed mounting screws)
- Metal trim angle adjustable up to 6°
- Upper handle includes integrated volume control and On/Off
- ADA compliant lever handles
- Includes service stops
- 7.1gpm at 45psi
- Requires GROHE Rapido® SmartBox (35 601 000) (sold separately)



PRODUCT FEATURES:



GROHE QuickFix®

GROHE TurboStat®

CERTIFICATIONS:

- Massachusetts Plumbing Board Approved
- N/A
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.10.1

AVAILABLE FINISHES:

24110000 GROHE StarLight® Chrome

241102430 Matte Black

24110A00 Hard Graphite

24110EN0

24110GN0 Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 04-11-2023

US

Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us.

Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



Brushed Nickel InfinityFinish™

GROHTHERM®

Pure Freude an Wasser GROHE

SINGLE FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

TECHNICAL DATA:

Product Height 6-1/4 in

Product Length 1-11/16 in

Product Width 6-1/4 in

