
Food Waste Disposers







- Distance from bottom of sink to center line of disposer outlet. Add 1/2" when stainless steel sinks are used.
- ** Length of tailpipe from center line of disposer outlet to end of tailpipe.

 NOTE: Plumb waste line to prevent standing water in disposer motor housing.

Job Specifications



Submittal Sheet

This model offers the following features and benefits:

- 1/3 Horsepower Heavy Duty Motor (Quiet Dura-Drive® Induction Motor)
- We Come To You® 1-Year In-Home Limited Warranty
- Rugged Galvanized Steel Construction (For Disposer Durability)
- Space-Saving Compact Design
- Available with or without a factory installed power cord.

Sample Specification

Food Waste Disposer(s) shall be InSinkErator Badger® 1, continuous feed, with 1/3 H.P. motor, galvanized steel grinding elements with two stainless steel 360° swivel lugs. Exclusive self-service wrench.

Available with or without a factory installed power cord.

Warranty:

1-Year parts and in-home service.

Specifications

| Type of Feed Continuous On/Off Control Wall Switch Motor Single Phase HP 1/3 Volts 120 HZ 60 RPM 1725 Amp. (Avg. Load) 5.6 Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Protection Manual Reset Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Yes Factory Installed Power Cord | | |
|---|------------------|---------------------------|
| Motor Single Phase HP 1/3 Volts 120 HZ 60 RPM 1725 Amp. (Avg. Load) 5.6 Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Yes Factory Installed Available with or without | Type of Feed | Continuous |
| HP 1/3 Volts 120 HZ 60 RPM 1725 Amp. (Avg. Load) 5.6 Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | On/Off Control | Wall Switch |
| Volts 120 HZ 60 RPM 1725 Amp. (Avg. Load) 5.6 Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) Weight (Approx.) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Yes Factory Installed Available with or without | Motor | Single Phase |
| HZ RPM 1725 Amp. (Avg. Load) 5.6 Time Rating Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Protection Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Dishwasher Drain Connection Yes Factory Installed Available with or without | HP | 1/3 |
| RPM 1725 Amp. (Avg. Load) 5.6 Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) Weight (Approx.) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Yes Factory Installed Available with or without | Volts | 120 |
| Amp. (Avg. Load) Amp. (Avg. Load) Time Rating Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Protection Average Water Usage Average Electrical Usage Average Electrical Usage Tain 1-1/2" Cushioned Slip Joint Testory Installed Available with or without | HZ | 60 |
| Time Rating Intermittent Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | RPM | 1725 |
| Lubrication Permanently Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Approx. 1 Gallon per Person Per Day Average Set Overload Average 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | Amp. (Avg. Load) | 5.6 |
| Lubricated Upper & Lower Bearings Shipping 12 lbs. 10 oz. (without cord) 12 lbs. 10 oz. (with cord) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Manual Reset Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | Time Rating | Intermittent |
| Weight (Approx.) 12 lbs. 14 oz. (with cord) Unit Finish Condor Grey Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Overload Average Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | Lubrication | Lubricated Úpper & |
| Overall Height 11-1/2" Grind Chamber Capacity 26 oz. Motor Overload Average Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | | |
| Grind Chamber Capacity 26 oz. Motor Protection Average Water Usage Average Electrical Usage Drain Connection Dishwasher Drain Connection Dishwasher Drain Connection Available with or without | Unit Finish | Condor Grey |
| Capacity 26 oz. Motor Protection Manual Reset Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain 1-1/2" Cushioned Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | Overall Height | 11-1/2" |
| Protection Overload Average Water Usage Approx. 1 Gallon per Person Per Day Average Electrical Usage 3-4 KWh per Year Drain Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | | 26 oz. |
| Water Usage Person Per Day Average Electrical Usage 3-4 KWh per Year Drain 1-1/2" Cushioned Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | | |
| Electrical Usage 3-4 KWh per Year Drain 1-1/2" Cushioned Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | | |
| Connection Slip Joint Dishwasher Drain Connection Yes Factory Installed Available with or without | | 3-4 KWh per Year |
| Prain Connection Yes Factory Installed Available with or without | | |
| | | Yes |
| | | Available with or without |



Food waste disposers can provide an environmentally responsible alternative to transporting food waste to landfills. And they can help reduce greenhouse gas emissions. At capable wastewater treatment plants, food waste can be recycled to produce renewable energy. Additionally, capable wastewater treatment plants can process food waste into fertilizer. (Check the plant in your area.)













1-800-558-5700 www.insinkerator.com The Emerson logo is a trademark and service mark of Emerson Electric Co. The mounting collar configuration is a trademark of Emerson Electric Co.

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

^{*} The complete InSinkErator warranty is included in the Care & Use Booklet packed with each unit.