

General	
Status	Active
Watts	13
Fluorescent Equivalent	31
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.5
Finish	Frosted
CCT (Kelvin)	4000
Temperature	Cool White
CRI	80
Lumens	1900
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	U-Bend
Technology	LED
Electrical	

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast bypass (Type B)
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

Physical	
MOL	22.59
MOD	1
Leg Spacing	1.63
Lens Finish	White
Lens Material	Plastic
Housing Color	White

Additional Information		
Warranty	5 Year Limited	
Compliance		
Safety Listing	cULus Listed for Type A; cULus Classified for Type B	
Location Rating	Damp	
Energy Star	No	
DLC Approved	Yes	
DLC ID	PL5RVLSB571D	
CEC Status	Lawful for sale in California	
RoHS Compliant	Yes	

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>









Notes

FCC Compliant Yes

NSF Approved

No - Not Approved











