

INSTALLATION INSTRUCTIONS

Tools Needed

- Screwdriver • Drill & Bits • Level • • Plumbers Basin Wrench to secure Faucet (Optional) • Wrench • Pencil • Tape Measure • Plumbers Putty •

Be sure to re-inforce wall before installation. We recommend a 2"x12" securely fastened to wall studs at the desired height for your installation.



Mounting Hardware



Wall Hung Installation


**** Be sure water supply is turned off before beginning.**

1. Determine the height you want. Place basin against the wall. Use a level to make sure both sides are level. Mark location on wall for mounting holes on back of sink.
2. Position each metal mounting bracket against the underside rear of basin and against the wall. Mark the location of mounting bracket holes on the wall.
3. Remove the basin from the wall. **Wall should be reinforced before continuing.**
4. Start to drill hole in **2"x12" re-inforced wall** for mounting hardware. Screw large wood screws provided into wall.
5. Before replacing basin, it would be convenient at this point to mount the faucet according to the manufacturer's instructions.
6. Slide sink onto bolts and ensure that it is level. Slide plastic flange washers and metal washers onto bolts. Thread hex nuts on snugly.
7. Hold basin on wall brackets and ensure that it is level. Secure sink to wall using bolts through holes in back of sink.
8. Connect all supply tubes to the faucet. Connect trap and drain assembly as described by the manufacturer.

NOTE: Determine whether your installation requires **Hangers** (pair) or a **Bracket** (one). These can be purchased separately to provide added support.



Bracket



Hangers

DO NOT over tighten or you may damage basin.