
# LED puck







Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
LEDRDP18	Ø2.75″	1.4 W	100 lm	130 lm	80	3000 K	12 V

# Specifications

12V DC LED driver required Over 50,000 hours of service life 12" input lead with quick connector 24" interconnection harness included Warm white light output Superior LED performance and lifespan Smooth 360° wide spread Minimal heat emission Surface adapter included Frosted lens Refer to website for dimmer compatibility 5-year warranty Kits available

# Note

Plug-in or hard-wired power supply required for installation. Sold separately

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALS representative for more information.

## Power supplies: plug-in

ETR-LED10WPI 12VDC/10W class 2 LED driver

ETR-LED24WPI 12VDC/24W class 2 LED driver

#### Power supplies: hard-wired

**BT06DIM-IC** 6W dimmable LED hardwire driver

**BT12DIM-IC** 12W dimmable LED hardwire driver

**BT24DIM-IC** 24W dimmable LED hardwire driver

**BT36DIM** 36W dimmable LED hardwire driver

**BT48DIM** 48W dimmable LED hardwire driver

# Finish



# Accessories

**4000E-24** 24" extension cord


**4000E-60** 60" extension cord

4000HRNS-24 24" interconnection harness

## Order example

#### LEDRDP18-WH

LEDRDP18 single puck with a 1.4W LED array with 100 lumens at 3000K in a white finish







Accent | dals.com 41