KFF-1610

SPECIFICATION SHEET

Single Handle Commercial Style Pull Down Kitchen Filter Faucet

Faucet Dimensions

Overall Height: 19 1/4" Spout Height: 6 3/8" Spout Reach: 8 5/8"

Features

- Commercial Style Pull Down Non-air gap Filter Faucet
- Metal Body
- · ABS Sprayer
- Lead Free Braided Nylon Waterway
- 360° Swivel Spout
- Faucet Flow Rate: 1.8 gpm (6.8L/min) @ 60 psi
- Filter Flow Rate: 1.0 gpm (3.8L/min) @ 60 psi
- Dual Function Sprayhead Spray/Stream
- 35mm Ceramic Cartridge
- 30" Integrated Nylon Waterlines
- Dome Shaped Screen Washer
- · Quick Weight
- Quick Connect Sprayer Hose
- Swivel Sprayer Connector
- 16" Hose Length
- Connections 3/8" Compression
- Max Deck Thickness: 3 1/2"
- TPI of aerator in the Sprayer M24*1
- 3/8" Tube Filter Connection
- Single Handle Operation for Faucet and Filter

Accessories Included

- · Weight
- Hex Wrench
- 3/8" to 1/4" Filter Connector

Available Finishes

- Chrome
- Matte Black
- Spot Free Stainless Steel
- Spot Free Antique Champagne Bronze
- Brushed Brass
- Brushed Brass/Matte Black
- Spot Free Stainless Steel/Matte Black

CODES/STANDARDS:


Product Certification

cUPC (ASME A112.18.1/CSA B125.1) NSF/ANSI Standard 61 and 372 certified by IAPMO AB1953, MASS, DOE, CEC, ADA

NOTE: Some Kitchen Faucets that do not have a pull out or pull down sprayer may be connected to a portable dishwasher. Pull out and pull down faucets should never be connected to portable dishwashers because potential pressure fluctuations during washing cycles cause hose ruptures or leaks.

Kraus Limited Lifetime Warranty see website for details www.kraususa.com

Kraus USA Customer Service 1.800.775.0703 | customerservice@kraususa.com



3/8" filter tube

2 1/8" [54.0mm]



