



#### PRODUCT DESCRIPTION

Combining a timeless, balanced shape with inward-facing directional lighting is sheer Brilliance™. The front-lit design of this modern, slim-profile mirror elevates task lighting to a level never before seen.

#### SPECIFICATION STATEMENT

Solution shall consist of a round or oval lighted mirror with integrated one-touch dimming and one-touch wall glow. LEDs will be mounted in a 45° channel in the frame of the mirror, with inward-facing directional lighting on the front face of the mirror and ambient wall glow behind the mirror. LEDs will be covered by an integrated diffuser and shall have an L<sub>70</sub> calculated life of 140,000 hours, with a greater than or equal to 90 CRI (color rendering index). Product shall incorporate a driver enclosure that is to be mounted to the back of the mirror. Product will have a 7-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

#### FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant DuraMirror™ glass
- One-touch dimmable inward-facing task lighting for brilliant facial illumination
- One-touch dimmable wall-glow ambient lighting with diffuser for a finished side view
- Greater illuminance with half the power consumption of traditional LED mirrors
- Sleek and modern profile
- Matte black finish standard
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Patent pending
- Designed in the USA

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 252 lumens per foot (front light)
- 468 lumens per foot (wall glow)
- Maximum 100 lumens per watt efficacy
- Calculated L<sub>70</sub> 36,000-hour LED lifespan
- Built-in EMX diffusers

#### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

**INSTALLATION SPECIFICATIONS**

- 120V hardwire electrical connection; junction box required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by capacitive touch button on fixture or non-dimming on/off wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

**MODELS**

Base Model*	Dimensions	Power Requirements
BRI-30-01L	30" diameter x 2.13"D (762mm x 54mm)	120V, 71W
BRI-36-01L	36" diameter x 2.13"D (914mm x 54mm)	120V, 84W
BRI-2436-01L	24.00"W x 36.00"H x 2.13"D (610mm x 914mm x 54mm)	120V, 71W

\*Base model number shown only. To specify additional options, contact Electric Mirror at [sales@electricmirror.com](mailto:sales@electricmirror.com).

**DIMENSIONAL DRAWING** *(Not to scale.)*

