

Submitted Model No.:

Specific Features:

Min. 2 1/2" (64 mm) Clearance to Back Splash 5 1/16" (129 mm) 2 9/16" (65 mm) 9 9/16" (243 mm) 6 1/8" (156 mm) 2 1/8" (54 mm) 1 1/4" - 1 1/2" 3" (76 mm) Max Deck Thickness (32-38 mm) Hole Size 30 5/16" (770 mm) 47" (1194 mm) 3/81 Compression Fittings

▲ Designate proper finish suffix

BRIZO

COLD WATER DISPENSER

- Single Handle Deck Mount
- Integrated Supply Tubes
- Integrated Air Gap

FEATURES:

Diamond Seal® Technology

STANDARD SPECIFICATIONS:

- Laminar water stream with max flow rate 1.5 gpm @ 60 psi,
- Works with RO systems, filtered water systems, or as a cold water tap
- Spout swings 360°
- Single lever handle design
- Air gap included with 1/4" tube for RO system and 3/8" tube
- Integrated supply tube with 3/8" compression fitting

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.6

 | Indicates compliance to ICC/ANSI A117.1
- Verified compliant with .25% weighted average Pb content regulations.