PHYLRICH®

Defining Luxury Since 1959

184-48

UPC

Deck Tub Set w/ Hand Shower



TECHNICAL DETAILS

ADA Compliance: No Deck Thickness Maximum: 2" Deck Thickness Minimum: 1/8" Fitting Hole Diameter: 1 1/8" Number of Holes: Five Hole Number of Handles: Three Hand Shower Flow Restriction: 1.8 GPM Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Spout Reach: 9 1/2" Spout Height: 8 1/4" Inlet Connection Type: Male 3/4" NPT Installation Type: Deck Mounted Primary Material: Brass Valve Material: Ceramic Spout Flow Restriction: Full Flow Hand Shower Flow Restriction: 1.8 GPM Water Pressure Maximum: 85 PSI Water Pressure Minimum: 20 PSI Water Pressure Recommended: 60 PSI

PRODUCT FEATURES

- Style: Contemporary
- Collection: Diama
- Temperature Controlled By Handles
- Blade Handles

CODES & STANDARDS

ASME A112.181/ CSA B1251, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC, Watersense 61 Sect. 9, State of MA.

WARRANTY

Mechanical Warranty: 10 Years from date of purchase. finish warranty: see catalog for further information.



