TL960DDLQ

Soirée® Widespread Lavatory High-Efficiency Faucet, 1.5 gpm

FEATURES

- WaterSense certified low-flow 1.5 gpm faucet
- Lever handles
- Solid brass construction
- · Ceramic disk valve cartridge
- Accommodates 8" -16" spread
- · Metal pop-up drain assembly included



COLORS/FINISHES

- #CP Polished Chrome
- #BN Brushed Nickel
- #PN Polished Nickel

CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1, NSF 61-9
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative compliance: California AB1953, Vermont S.152 & Maryland HB. 372, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant







PRODUCT SPECIFICATION

The widespread lavatory faucet shall have a maximum flow rate of 1.5 gpm (5.7 lpm). Product shall have lever handles. Product shall have a solid brass construction. Product shall have a ceramic disk valve cartridge. Product shall accomodate 8"-16" spread. Product shall include metal pop-up drain assembly. Product shall be compliant with California AB1953, Vermont S.152 & Maryland HB. 372. Product shall be TOTO Model TL960DDLQ#

Soirée® Widespread Lavatory High-Efficiency Faucet, 1.5 gpm

SPECIFICATIONS

Warranty Lifetime Limited Warranty

(Residential Use)

One Year (Commercial Use)

Material BrassShipping Weight 11.5 lbs.

Shipping Dimensions 20-1/2"L x 9-3/4"W x

3-1/2"H

• Maximum Flow Rate 1.5 gpm (5.7 lpm)



