



Mirror with lighting	Dimension	Weight	Order number
cIAPMO®ELECTRICAL, 1 sensor switch bottom right, Mirrors require a GFCI 110 V 60 Hz power source. Flat plug will be supplied with mirror, LED (life span > 30,000 hours), LED module permanently enclosed, LED module 3500 kelvin light color, 11 W			
Colors			
M03 Jade High Gloss Lacquer M10 Apricot Pearl High Gloss Lacquer M12 Brushed Oak (Real wood veneer) M13 American Walnut (Real wood veneer) M14 Terra (Decor) M18 White Matt M20 VSG Picto White M22 White High Gloss (Decor) M27 White Lilac High Gloss Lacquer M31 Pine Silver (Decor) M38 Dolomiti Grey High Gloss Lacquer M40 Black High Gloss Lacquer M43 Basalt Matt (Decor) M47 Stone Blue High Gloss Lacquer M49 Graphite Matt (Decor) M51 Pine Terra (Decor) M52 European Oak (Decor) M53 Chestnut Dark (Decor) M61 Olive Brown High Gloss Lacquer M69 Brushed Walnut (Real wood veneer) M71 Mediterranean Oak (Real wood veneer) M72 Brushed Dark Oak (Real wood veneer) M73 Ticino Cherry Tree (Decor) M79 Natura Walnut (Decor) M85 White High Gloss Lacquer M86 Cappuccino High Gloss Lacquer M87 White Lilac Satin Matt Lacquer M89 Flannel Grey High Gloss Lacquer M90 Flannel Grey Satin Matt Lacquer			
Variant			
	17 3/4" x 4 1/8" Ir	nch	XL7290
Infobox			
Distance between sensor and reflecting surfaces = minimum 3'	ı		
Additional modules cIAPMO®ELECTRICAL, LED dimming function			UV9980

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.