

Vero Mirror cabinet # VE7500L0000

|< 23 5/8" Inch >|



cIAPMO®ELECTRICAL, 1 mirror door, 1 glass shelf, 1 wooden shelf with rail cover, 1 cosmetic mirror, 1 sensor switch bottom right, LED (life span > 30,000 hours), LED module permanently enclosed, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site), Mirror cabinets require a GFCI 110 V 60 Hz power source. Flat plug will be supplied with the mirror		
right, LED (life span > 30,000 hours), LED module permanently enclosed, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site), Mirror cabinets require a GFCI 110 V		
(GFCI outlets can be added to the cabinet by a certified electrician on the job site), Mirror cabinets require a GFCI 110 V		
electrician on the job site), Mirror cabinets require a GFCI 110 V		
60 Hz power source. Flat plug will be supplied with the mirror		
cabinet, LED module 3500 kelvin light color, 11 W		
Colors		
M00		
Variant		
23 5/8" x 5 3/4" Inch		VE7500L0000
Infobox		
Distance between sensor and reflecting surfaces = minimum 3", Required specification for ((L) or right (R)	ordering: - Hinges left	
Additional modules cIAPMO®ELECTRICAL, LED dimming		
function		UV9980

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are nonbinding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.