


COLONY® SOFT PRESSURE BALANCE BATH/SHOWER FITTING WITH FloWise® SHOWERHEAD



T675.508 Bath/Shower Trim Shown

GENERAL DESCRIPTION:

SHOWERHEAD FloWise water saving showerhead offers 40% water savings at maximum 1.5 gpm/5.7 L/min. flow rate.

WALL TUB SPOUT

Metal slip-on diverter spout.

WALL VALVE TRIM


Available with metal lever handle. Plastic wall escutcheon.

MODEL NUMBER:

TRIM KITS:

- □ T675.508 Colony Soft BATH/SHOWER Trim Kit Metal Lever Handle. FloWise Showerhead. LESS Valve Body.
- □ T675.507 Colonv Soft SHOWER ONLY Trim Kit Metal Lever Handle. FloWise Showerhead. LESS Valve Body.

For use with R120 Series Pressure Balance Valves. See reverse side for available Rough Valves.



SUGGESTED SPECIFICATION:

Bath/shower fitting shall feature FloWise water saving showerhead with Max. 1.5 gpm/5.7 L/min. flow rate. Fitting shall be: American Standard - Trim Kit Model # T675.50_.___. and Valve Body Model # R12_.



COLONY® SOFT PRESSURE BALANCE BATH/SHOWER FITTING WITH FloWise® SHOWERHEAD

8

6

4 2 (

20

40

*Flow rates shown are for mixed hot and cold.

GALLONS PER MINUTE

FLOW RATE*

60

INLET PRESSURE (PSI)

Spout Shower

100


80

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A 117.1 ASSE 1016 ASME A112.18.1 CSA B 125.1





*To modify a product, add suffix after the 4th digit (ex. T064<u>ITP</u>502.002)

FRIM KITS *		* TRIM & ROUGH MUST BE ORDERED SEPARATELY.		Finish Options	
	Product		Polished Chrome	PVD Satin Nickel	
	Number	Description	002	295	
	T675.508	Bath/Shower Trim Kit. Metal Lever Handle. FloWise Showerhead. LESS Valve Body.			
	T675.507	Shower Only Trim Kit. Metal Lever Handle. FloWise Showerhead. LESS Valve Body.			

	Product Number	Description
	R121	Rough Valve Body less trim. Universal inlets/outlets.
SE	R121SS	Rough Valve Body less trim. Universal inlets/outlets with Screwdriver Stops.
	R120	Rough Valve Body less trim. Direct Sweat inlets/outlets.
BO	R120SS	Rough Valve Body less trim. Direct Sweat inlets/outlets with Screwdriver Stops.
LVE	R125	Rough Valve Body less trim. Female Thread inlets/outlets.
Ţ	R125SS	Rough Valve Body less trim. Female Thread inlets/outletswith Screwdriver Stops.
1	R127	Rough Valve Body less trim. PEX inlets/universal outlets for Crimp Ring PEX system (ASTM F1807).
OUGH	R127SS	Rough Valve Body less trim. PEX inlets/universal outlets for Crimp Ring PEX system (ASTM F1807) with Screwdriver Stops.
	R128	Rough Valve Body less trim. PEX inlets/universal outlets for Cold Expansion PEX system (ASTM F1960).
	R128SS	Rough Valve Body less trim. PEX inlets/universal outlets for Cold Expansion PEX system (ASTM F1960) with Screwdriver Stops.
	R129	Rough Valve Body less trim. CPVC inlets/universal outlets.
	R129SS	Rough Valve Body less trim. CPVC inlets/universal outlets with Screwdriver Stops.

Meets the American Disabilities Act Guidelines and ANSI A117.1 Ł

Requirements for the physically challenged.