


SPECIFICATION SHEET

Series:	Pressure Reduction Valve		
Model:	SB40 /SB60		
Part no.	SB40	Finish:	Gray
Part no.	SB60	Finish:	Gray



Description	
Features	
Flow:	4 gpm @ 100 PSI
Spray:	Full Spray
Cartridge:	n/a
Swivel:	n/a
Recommended Water Pressure:	30-125 PSI
Max. Water Pressure:	300 PSI
Hole Size for Faucet:	n/a
Optional accessories:	
Base Plate:	n/a
Soap Dispenser:	n/a
Little Butler Faucet:	All Franke Models
Other:	Recommended for Chiller & Heating Tank

Detail	
List Price SB40	\$ 32.00
List Price SB60	\$ 32.00
Technology	
Pressure Reduction Valve SB40 or SB60 recommended for Chiller CT-200 and Heating tank HT-200	
Compliance	
Certified in compliance with NSF 61, NSF372 & AB1953	




Dimension Drawing

ASV SERIES SPECIFICATIONS			
Model	PSI Specification	Inlet Pressure (PSI)	Outlet Pressure (PSI)
SB-FPV-40	40	100	40
	40	150	44
	40	200	50
SB-FPV-60	60	100	60
	60	150	64
	60	200	70