

Cheviot

INSTALLATION INSTRUCTIONS

Console Sinks

Tools Needed:

1. Screwdriver
2. Drill and drill bits (not supplied)
3. Lag bolts
4. Level
5. White or clear silicone
6. Wrench set
7. Pencil



Notes:

1. Three people are required to install the console. The console top weighs approximately 120 lbs.
2. Mounting hardware must be adequate for the type of wall. If lag bolts are used, install a wooden horizontal mounting board between the studs in the wall. This will serve as a supporting base for the mounting hardware.

Installation:

1. Place the console upside down on a piece of packing cardboard to prevent scratching.
2. Place a bead of silicone around the top of each leg.
3. Place each leg into the sockets in the front of the console top. Make sure the legs are firmly set into each socket. It is best to let the silicone dry for 24 hours to let the legs set.
4. After 24 hours, stand the console assembly up and support it against the wall.
5. Two people should hold the console top in place. The other person should use a level on the back and side edges to help position the top both side-to-side and front-to-back correctly.
6. Use the pencil to mark the mounting hole positions on the wall.
7. Move the console away from the wall and set it aside. Drill pilot holes in the wall.
8. Install the lag bolts in the wall as appropriate.
9. Place the console top with legs against the wall and install using the lag bolts. Tighten the bolts only loosely.
10. Two people should slightly lift up the front of the console and legs. The second person should apply a small amount of silicone to the bottom of each leg to prevent the legs from moving after installation.
11. Completely tighten the 2 lag bolts attaching the console to the wall. Be careful not to over-tighten. **Do not tighten the lag bolts too much or you may damage the console.**