

4U Series LED Collection

8" LED Cabinet Light in BZT

4U27K08BZT

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	1.00"
Length	8.00"
Width	4.50"

Ordering Information

Product ID	4U27K08BZT
Available Finishes	BZT, WHT
Collection	4U Series LED Collection

Dimensions

Weight	0.90 LBS
--------	----------

Photometrics

Kelvin Temperature	2700K
Color Rendering Index	93
Volt AMPERE	2.80

Specifications

Material	Aluminum
Glass Description	Frosted

Electrical

Dimmable	Yes
Voltage	108-132V

Qualifications

Safety Rated	Dry
Title 24	Yes
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Installation

Wire Connectors	Wire Nuts
Direct Wire	Yes
Knockouts	0.5"
Number of Knockouts	4
Modular	Yes

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Delivered Lumens	177
Delivered Efficacy	49
Dimming	Yes

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

4U Series LED Collection

8" LED Cabinet Light in WHT

4U27K08WHT (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	1.00"
Length	8.00"
Width	4.50"

Ordering Information

Product ID	4U27K08WHT
Finish	Textured White
Available Finishes	BZT, WHT
Collection	4U Series LED Collection

Dimensions

Weight	0.90 LBS
--------	----------

Photometrics

Kelvin Temperature	2700K
Color Rendering Index	93
Volt AMPERE	2.80

Specifications

Material	Aluminum
Glass Description	Frosted

Electrical

Dimmable	Yes
Voltage	108-132V

Qualifications

Safety Rated	Dry
Title 24	Yes
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Installation

Wire Connectors	Wire Nuts
Direct Wire	Yes
Knockouts	0.5"
Number of Knockouts	4
Modular	Yes

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Delivered Lumens	177
Delivered Efficacy	49
Dimming	Yes

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

4U Series LED Collection

8" LED Cabinet Light 3000K in BZT

4U30K08BZT

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	1.00"
Length	8.00"
Width	4.50"

Ordering Information

Product ID	4U30K08BZT
Available Finishes	BZT, WHT
Collection	4U Series LED Collection

Dimensions

Weight	0.90 LBS
--------	----------

Photometrics

Kelvin Temperature	3000K
Color Rendering Index	94
Volt AMPERE	2.90

Specifications

Material	Aluminum
Glass Description	Frosted

Electrical

Dimmable	Yes
Voltage	108-132V
Input Voltage	Single 120
Operating Voltage Range	108-132V

Qualifications

Safety Rated	Dry
Title 24	Yes
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Installation

Wire Connectors	Wire Nuts
Direct Wire	Yes
Knockouts	0.50"
Number of Knockouts	4
Modular	Yes

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Delivered Lumens	187
Delivered Efficacy	53
Dimming	Yes

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

4U Series LED Collection

8" LED Cabinet Light 3000K in WHT

4U30K08WHT (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	1.00"
Length	8.00"
Width	4.50"

Ordering Information

Product ID	4U30K08WHT
Finish	Textured White
Available Finishes	BZT, WHT
Collection	4U Series LED Collection

Dimensions

Weight	0.90 LBS
--------	----------

Photometrics

Kelvin Temperature	3000K
Color Rendering Index	94
Volt AMPERE	2.90

Specifications

Material	Aluminum
Glass Description	Frosted

Electrical

Dimmable	Yes
Voltage	108-132V
Input Voltage	Single 120
Operating Voltage Range	108-132V

Qualifications

Safety Rated	Dry
Title 24	Yes
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Installation

Wire Connectors	Wire Nuts
Direct Wire	Yes
Knockouts	0.50"
Number of Knockouts	4
Modular	Yes

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Delivered Lumens	187
Delivered Efficacy	53
Dimming	Yes

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.