

120V LED 12.5W 10 Deg S 30K AZT

16200AZT30 (Textured Architectural Bronze)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Ordering Information

Product ID	16200AZT30
Finish	Textured Architectural Bronze
Available Finishes	AZT, AZT, BBR, BBR, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	3000K
Color Rendering Index	80

Specifications

Material	Aluminum
Glass Description	10 Beam Spread Optic

Electrical

Voltage	120VAC
Operating Voltage Range	108-130 VAC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	12.5W

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

120V LED 12.5W 10 Deg S 42K AZT

16200AZT42 (Textured Architectural Bronze)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Ordering Information

Product ID	16200AZT42
Finish	Textured Architectural Bronze
Available Finishes	AZT, AZT, BBR, BBR, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	4250K
Color Rendering Index	75

Specifications

Material	Aluminum
Glass Description	10 Beam Spread Optic

Electrical

Voltage	120VAC
Operating Voltage Range	108-130 VAC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	12.5W

Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

120V LED 12.5W 10 Deg S 30K BBR

16200BBR30 (Bronzed Brass)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Ordering Information

Product ID	16200BBR30
Finish	Bronzed Brass
Available Finishes	AZT, AZT, BBR, BBR, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	3000K
Color Rendering Index	80

Specifications

Material	Brass
Glass Description	10 BEAM SPREAD OPTIC
Shade Dimensions	10 BEAM SPREAD OPTIC

Electrical

Voltage	120VAC
Operating Voltage Range	108-130 VAC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	12.5W

Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

120V LED 12.5W 10 Deg S 42K BBR

16200BBR42 (Bronzed Brass)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Ordering Information

Product ID	16200BBR42
Finish	Bronzed Brass
Available Finishes	AZT, AZT, BBR, BBR, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	4250K
Color Rendering Index	75

Specifications

Material	Brass
Glass Description	10 Beam Spread Optic

Electrical

Voltage	120VAC
Operating Voltage Range	108-130 VAC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	12.5W

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

120V LED 12.5W 10 Deg S 3000K

16200WHT30 (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Ordering Information

Product ID	16200WHT30
Finish	Textured White
Available Finishes	AZT, AZT, BBR, BBR, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	3000K
Color Rendering Index	80

Specifications

Material	Aluminum
Glass Description	10 Beam Spread Optic

Electrical

Voltage	120VAC
Operating Voltage Range	108-130 VAC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	12.5W

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

120V LED 12.5W 10 Deg S 4250K

16200WHT42 (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Ordering Information

Product ID	16200WHT42
Finish	Textured White
Available Finishes	AZT, AZT, BBR, BBR, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	4250K
Color Rendering Index	75

Specifications

Material	Aluminum
Glass Description	10 Beam Spread Optic

Electrical

Voltage	120VAC
Operating Voltage Range	108-130 VAC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Primary Lamping

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	12.5W

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.