


TL993SE

Neorest[®] II Lavatory Faucet

FEATURES

- Electronic faucet
- Adjustable temperature with on-deck handle
- Temperature indicating LED light on handle
- Cascading laminar flow
- Two flow rates (2.0/1.3 gpm)
- SMA antiscald thermostatic mixing valve
- Grid drain not included



COLORS/FINISHES

• #CP Polished Chrome

CODES/STANDARDS

- Meets and exceeds ASME A112.18.1/CSA B125.1, NSF 61-9, ASSE 1070, UL 1951, CSA C22.2#14
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB1953 & Vermont S.152




PRODUCT SPECIFICATION


The electronic faucet shall have an adjustable temperature with on-deck handle, temperature indicating LED light on handle and be compliant with California AB1953 & Vermont S.152. Product shall have electrical components separated from spout assembly and sealed in waterproof compartments. Product shall have a 2 flow rates of 2.0 or 1.3 gallons per minute. Product shall be TOTO Model TL993SE#CP.

Neorest[®] II Lavatory Faucet

SPECIFICATIONS

- Cast Brass Material
- Operating pressure range
 - Min. Pressure: 10 psi (0.07 Mpa) Max. Pressure: 80 psi (0.55 Mpa)
- Recommended pressure range
- Water supply temp
- 30 psi 44 psi (0.2-0.3 MPa) Cold: 39°F-80°F(4°C-27°C) Hot: 120°F-180°F(49°C-82°C)
- Flow Rate Options: (Adjustable with on-deck handle)
- 1) High Efficiency Setting: 1.3 gpm (5L/min) 2) Water Saving Setting 2.0 gpm (7.6L/min)
- Adjustable discharge water temp
- 93°F-112°F (34°C-44°C) Power Rating 100-240VAC 0.8Amax 50/60Hz (Proper installation requires a 15amp GFCI outlet connection)
- 1/2" NPSM Water inlet
- Warranty 3-Year Limited Warranty
- Shipping Dimensions 17-1/4"L x 13"W x
- 8-3/4"H 16.5 lbs.
- Shipping Weight





TOTO

These dimensions and specifications are subject to change without notice